

Data Analysis

with Stata

Cheat Sheet

For more info, see Stata's reference manual (stata.com)

Results are stored as either **i**-class or **e**-class. See [Programming Cheat Sheet](#)

Summarize data

Examples use `auto.dta` (`sysuse auto, clear`) unless otherwise noted

graph box `price, over(foreign)`

create box-and-whiskers plot

stem mpg

return stem-and-leaf display of mpg

summarize `price mpg, detail` ————— used commands are highlighted in yellow

calculate various univariate summary statistics

ci mean `mpg price, level(99)` ————— for Stata 13: `ci mpg price, level(99)`

compute standard errors and confidence intervals

correlate `mpg price`

return correlation or covariance matrix

pwcorr `price mpg weight, star(0.05)`

return all pairwise correlation coefficients with sig. levels

mean `price mpg`

estimates of means, including standard errors

proportion `rep78 foreign`

estimates of proportions, including standard errors for categories identified in varlist

ratio `price mpg`

estimates of ratio, including standard errors

total `price`

estimates of totals, including standard errors

Statistical tests

tabulate `foreign rep78, chi2 exact expected`

tabulate foreign and repair record and return χ^2 and Fisher's exact statistic alongside the expected values

ttest `mpg, by(foreign)`

estimate t test on equality of means for mpg by foreign

prtest `foreign == 0.5`

one-sample test of proportions

ksmirnov `mpg, by(foreign) exact`

Kolmogorov-Smirnov equality-of-distributions test

ranksum `mpg, by(foreign)`

equality tests on unmatched data (independent samples)

anova `systolic drug` **webuse** `systolic, clear`

analysis of variance and covariance

pwmean `mpg, over(rep78) pveffects mcompare(tukey)`

estimate pairwise comparisons of means with equal variances include multiple comparison adjustment

Estimation with categorical & factor variables

CONTINUOUS VARIABLES

measure something

CATEGORICAL VARIABLES

identify a group to which an observation belongs

INDICATOR VARIABLES

denote whether something is true or false

OPERATOR

i.

specify indicators

ib.

specify base indicator

fset

command to change base

c.

treat variable as continuous

o.

omit a variable or indicator

#

specify interactions

##

specify factorial interactions

EXAMPLE

`regress price i.rep78`

`regress price ib(3).rep78`

`fset base frequent rep78`

`regress price i.foreign#c.mpg i.foreign`

`regress price io(2).rep78`

`regress price mpg c.mpg#c.mpg`

`regress price c.mpg##c.mpg`

more details at <https://www.stata.com/manuals/u26.pdf>

geocenter.github.io/StataTraining

Disclaimer: we are not affiliated with Stata. But we like it.

Declare data

By declaring data type, you enable Stata to apply data munging and analysis functions specific to certain data types

TIME SERIES

tset `time, yearly`

declare sunspot data to be yearly time series



tsreport

report time-series aspects of a dataset

generate `lag_spot = L1.spot`

create a new variable of annual lags of sunspots

tsline

plot

time

series

of

sunspots

Number of sunspots

200

100

0

1950

1960

1970

1980

1990

e

arima `spot, ar(1)`

fit an autoregressive model with 2 lags

TIME-SERIES OPERATORS

L.

lag x_{t-1}

F.

lead x_{t+1}

D.

difference $x_t - x_{t-1}$

S.

seasonal difference $x_{t-12} - x_{t-24}$

L2.

2-period lag x_{t-2}

F2.

2-period lead x_{t+2}

D2.

difference of difference $x_{t-1} - x_{t-2} - (x_{t-3} - x_{t-4})$

S2.

lag-2 (seasonal difference) $x_{t-24} - x_{t-48}$

USEFUL ADD-INS

tscollap

compact time series into means, sums, and end-of-period values

carryforward

carry nonmissing values forward from one obs. to the next

tsspell

identify spells or runs in time series

SURVIVAL ANALYSIS

webuse `drugtr, clear`

stset `studytime, failure(died)`

declare survey design for a dataset



stsum

summarize survival-time data

stcox `drug age`

fit a Cox proportional hazards model

1 Fit models

stores results as **e-class**

regress `price mpg weight, vce(robust)`

fit ordinary least-squares (OLS) model

on mpg, weight, and foreign, apply robust standard errors

regress `price mpg weight if foreign == 0, vce(cluster rep78)`

regress price only on domestic cars, cluster standard errors

rreg `price mpg weight, genwt(rep78)`

estimate robust regression to eliminate outliers

probit `foreign turn price, vce(robust)`

estimate probit regression with robust standard errors

logit `foreign headroom mpg, or`

estimate logistic regression and report odds ratios

bootstrap, `reps(100): regress mpg /`

`/* weight gear foreign */`

estimate regression with bootstrapping

jackknife `r(mean): sum mpg`

jackknife standard error of sample mean

ADDITIONAL MODELS

pca ← built-in Stata command

principal components analysis

factor

factor analysis

poisson • **nbreg**

count outcomes

tobit

user-written censored data

ivregress

instrumental variables

difregress

difference in differences

rd

regression discontinuity

xtbdond

dynamic panel estimator

teffects

propensity-score matching

synth

synthetic control analysis

oaxaca

Blinder-Oaxaca decomposition

PANEL / LONGITUDINAL

xset `id year`

declare national longitudinal data to be a panel

xtdescribe

report panel aspects of a dataset

xsum `hours`

summarize hours worked, decomposing standard deviation into between and within components

xline `ln_wage if id <= 22, tlabel(#3)`

plot panel data as a line plot

xtreg `ln_w c.age##c.age ttl_exp, fe vce(robust)`

fit a fixed-effects model with robust standard errors

webuse `nhanes2b, clear`

svyset `psuid [pweight = finalwgt], strata(stratid)`

declare survey design for a dataset

svydescribe

report survey data details

svy: mean `age, over(sex)`

estimate a population mean for each subpopulation

svy, subpop(rural): mean `age`

estimate a population mean for rural areas

svy: tabulate `sex heartatk`

report two-way table with tests of independence

svy: reg `zinc c.age##c.age female weight rural`

estimate a regression using survey weights

2 Diagnostics

estat `hettest` test for heteroskedasticity

ovtest test for omitted-variable bias

vif report variance inflation factor

Type `help regress postestimation plots` for additional diagnostic plots

dfbeta calculate measure of influence

rvpfplot, yline(0) plot residuals against fitted values

avplots plot all partial-leverage leverage plots in one graph

3 Postestimation commands that use a fitted model

regress `price headroom length` Used in all postestimation examples

display _b[length] return coefficient estimate or standard error for length from most recent regression model

margins, dydx[length] returns e-class information when post option is used

margins, dx0 return the estimated marginal effect for length

margins, eyex[length] return the estimated elasticity for length

predict `yhat if e(sample)` create predictions for sample on which model was fit

predict double resid, residuals calculate residuals based on last fitted model

test `headroom = 0` test linear hypotheses that headroom estimate equals zero

lincom `headroom - length` estimate linear combination (headroom - length)

Programming

with Stata

Cheat Sheet

For more info, see Stata's reference manual ([stata.com](#))

1 Scalars

both r- and e-class results contain scalars
scalar `x1 = 3`
create a scalar x1 storing the number 3
scalar `a1 = "I am a string scalar"`
create a scalar a1 storing a string

Scalars can hold
numeric values or
arbitrarily long strings

2 Matrices

e-class results are stored as matrices
matrix `a = (4\ 5\ 6)`
create a 3 x 1 matrix
matrix `b = (7, 8, 9)`
create a 1 x 3 matrix
matrix `d = b'` transpose matrix b; store in d
matrix `ad1 = a \ d`
row bind matrices
matselrc `b x, c(1 3)` search matselrc
select columns 1 & 3 of matrix b & store in new matrix x
mat2txt, **matrix(ad1) saving**(textfile.txt) **replace**
export a matrix to a text file
ssc install mat2txt

DISPLAYING & DELETING BUILDING BLOCKS

[scalar | matrix | macro | estimates] [list | drop] b
list contents of object b or drop (delete) object b

[scalar | matrix | macro | estimates] dir

list all defined objects for that class

matrix list b **matrix dir** **scalar drop** x1
list contents of matrix b list all matrices delete scalar x1

3 Macros

public or private variables storing text

GLOBAL available through Stata sessions **PUBLIC**

global pathdata "C:/Users/SantasLittleHelper/Stata"

define a global variable called pathdata

cd \$pathdata — add a \$ before calling a global macro

change working directory by calling global macro

global myGlobal price mpg length

summarize \$myGlobal

summarize price mpg length using global

LOCAL available only in programs, loops, or do-files **PRIVATE**

local myLocal price mpg length

create local variable called myLocal with the

strings price, mpg, and length

summarize `myLocal' add a ` before and a ` after local macro name to call

summarize contents of local myLocal

levelsof rep78, **local(levels)**

create a sorted list of distinct values of rep78,

store results in a local macro called levels

local varLab: variable label foreign can also do with value labels

store the variable label for foreign in the local varLab

TEMPVARS & TEMPFILES special locals for loops/programs

tempvar temp1 — initialize a new temporary variable called temp1

generate `temp1' = mpg^2 — save squared mpg values in temp1

summarize `temp1' — summarize the temporary variable temp1

tempfile myAuto create a temporary file to

see also
tempname

be used within a program

Building blocks basic components of programming

R- AND E-CLASS: Stata stores calculation results in two* main classes:
r return results from general commands such as **summarize** or **tabulate** **e** return results from estimation commands such as **regress** or **mean**

To assign values to individual variables, use:

- 1 SCALARS **r** individual numbers or strings
2 MATRICES **e** rectangular array of quantities or expressions
3 MACROS **e** pointers that store text (global or local)

* there's also s- and n-class

4 Access & save stored r- and e-class objects

Many Stata commands store results in types of lists. To access these, use **return** or **ereturn** commands. Stored results can be scalars, macros, matrices, or functions.

summarize price, detail

rreturn list

returns a list of scalars

scalars:
r(N) = 74
r(mean) = 6165.25...
r(var) = 86995225.97...
r(sd) = 2949.49...
...

Results are replaced each time an r-class / e-class command is called

scalars:
e(df_r) = 73
e(N_over) = 1
e(N) = 73
e(k_eq) = 1
e(rank) = 1

generate p_mean = r(mean)

create a new variable equal to average of price

preserve create a temporary copy of active data frame

restore restore temporary copy to point last preserved

set restore points to test code that changes data

ACCESSING ESTIMATION RESULTS

After you run any estimation command, the results of the estimates are stored in a structure that you can save, view, compare, and export.

regress price weight

estimates store est1

store previous estimation results est1 in memory

regress price weight mpg

estimates store est2

regress price weight mpg foreign

estimates store est3

fit two regression models and store estimation results

etable, estimates(est1 est2 est3) column(index) /*

***showstars showstarsnote**

print a table of the three estimation results

Use **estimates store** to compile results for later use

EXPORTING RESULTS

etable, estimates(est1 est2 est3) column(index) /*

***showstars showstarsnote export(autoreg.txt)**

export table to a text file

The collect suite of commands allows further customization of tables. Also see **putdocx** and **putexcel** for exporting tables, images, and text.

Additional programming resources

bitly/statacode

download all examples from this cheat sheet in a do-file

ado update

Update user-written ado-files

net install package, from (<https://raw.githubusercontent.com/username/repo/master>)

install a package from a Github repository

s https://github.com/andreweheiss/SublimeStataEnhanced

configure Sublime text for Stata 11-15

Loops: Automate repetitive tasks

ANATOMY OF A LOOP

Stata has three options for repeating commands over lists or values: **foreach**, **forvalues**, and **while**. Though each has a different first line, the syntax is consistent:

objects to repeat over
foreach x of varlist var1 var2 var3 { open brace must appear on first line
temporary variable used only within the loop
requires local macro notation
command "x", option command(s) you want to repeat
can be one line or many
...
}
close brace must appear on final line by itself

FOREACH: REPEAT COMMANDS OVER STRINGS, LISTS, OR VARIABLES

foreach x in of [local, global, varlist, newlist, numlist] {

Stata commands referring to 'x'
}

list types: objects over which the commands will be repeated

STRINGS

foreach x in auto.dta auto2.dta {

sysuse "auto.dta", clear
tab rep78, missing

same as...
sysuse "auto.dta", clear
tab rep78, missing

LISTS

foreach x in "Dr. Nick" "Dr. Hibbert" {

display length("Dr. Nick")

display length("Dr. Hibbert")

When calling a command that takes a string, surround the macro name with quotes.

VARIABLES

foreach x in mpg weight {

summarize x
}

must define list type
foreach in takes any list as an argument with elements separated by spaces
foreach of requires you to state the list type, which makes it faster
summarize mpg
summarize weight

FORVALUES: REPEAT COMMANDS OVER LISTS OF NUMBERS

forvalues i = 10(10)50 {

display i
}

numeric values over which loop will run
display 10
display 20
...

ITERATORS

i = 10/50 → 10, 11, 12, ...

i = 10(10)50 → 10, 20, 30, ...

i = 10 20 to 50 → 10, 20, 30, ...

Use display command to show the iterator value at each step in the loop

display 10
display 20
...

DEBUGGING CODE

set trace on (off)

trace the execution of programs for error checking

PUTTING IT ALL TOGETHER

sysuse auto, clear

generate car_make = word(make, 1) — pull out the first word from the make variable

levelsof car_make, **local(cmake)** — calculate unique groups of car_make and store in local cmake

local i = 1

local cmake_len : word **count** `cmake' — store the length of local cmake in local cmake_len

foreach x of **local** cmake {

display in yellow "Make group `i' is `x'"

if `i' == `cmake_len' {

display "The total number of groups is `i'"

}

local i = `++i' — increment iterator by one

Data Processing

with Stata

Cheat Sheet

For more info, see Stata's reference manual (stata.com)

Useful shortcuts

Note: not applicable with Stata for Mac.

F2 — keyboard buttons

describe data

Ctrl + **8**

open the Data Editor

clear

delete data in memory

AT COMMAND PROMPT

PgUp

PgDn

scroll through previous commands

Tab

autocompletes variable name after typing part

cls

clear the console (where results are displayed)

Setup

pwd

print current (working) directory

cd "C:\Program Files\Stata19"

change working directory

dir

display filenames in working directory

dir *.dta

List all Stata data in working directory

capture log close

close the log on any existing do-files

log using "myDoFile.txt", replace

create a new log file to record your work and results

search mdesc

find the package mdesc to install

packages contain extra commands that expand Stata's toolkit

ssc install mdesc

install the package mdesc; needs to be done once

Import data

sysuse auto, clear

load system data (auto data)

for many examples, we use the auto dataset.

use "yourStataFile.dta", clear

load a dataset from the current directory

frequently used commands are highlighted in yellow

import excel "yourSpreadsheet.xlsx", /*

*** /sheet("Sheet1") cellrange(A2:H11) firstrow**

import delimited "yourFile.csv", /*

*** /rowrange(2:11) colrange(1:8) varnames(2)**

import sas "yourSASfile.sas7bdat", bcat("value labels file")

import spss "yourSPSSfile.sav"


webuse set "https://github.com/GeoCenter/StataTraining/raw/master/Data2/Data"

webuse "wb_indicators_long"

set web-based directory and load data from the web

Basic syntax

All Stata commands have the same format (syntax):



To find out more about any command-like what options it takes-type **help command**

Basic data operations

Arithmetic

+ add (numbers)
+ combine (strings)
- subtract
* multiply
/ divide
^ raise to a power

Logic

& and
! or ~ not
| or

if foreign != 1 & price >= 10000

make	foreign	price
Chevy Colt	0	3,984
Buick Riviera	0	10,372
Honda Civic	1	4,499
Volvo 260	1	11,995

== tests if something is equal
= assigns a value to a variable

== equal
< less than
!= not or
~ equal
<= less than or equal to
> greater than
>= greater or equal to

if foreign != 1 | price >= 10000

make	foreign	price
Chevy Colt	0	3,984
Buick Riviera	0	10,372
Honda Civic	1	4,499
Volvo 260	1	11,995

Explore data

VIEW DATA ORGANIZATION

describe make price
display variable type, format, and any value/variable labels

count

count if price > 5000
number of rows (observations) can be combined with logic

ds, has(type string)

lookfor "in."
search for variable types, variable name, or variable label

isid mpg

check if mpg uniquely identifies the data

BROWSE OBSERVATIONS WITHIN THE DATA

browse

open the Data Editor

list make price if price > 10000 & !missing(price) **clist** ... (compact form)

list the make and price for observations with price > \$10,000

display price[4]

display the 4th observation in price; only works on single values

gsort price mpg (ascending)

gsort -price -mpg (descending)

sort in order, first by price then miles per gallon

duplicates report

finds all duplicate values in each variable

levelsof rep78

display the unique values for rep78

Missing values are treated as the largest positive number. To exclude missing values, ask whether the value is less than " ".

assert price!=.
verify truth of claim

Change data types

Stata has six data types, and data can also be missing:
no data true/false words numbers
missing **byte** **string** **int long float double**

To convert between numbers and strings:

1 **gen** foreignString = **string**(foreign)
tostring foreign, **gen**(foreignString)
decode foreign, **gen**(foreignString) "foreign"

1 **gen** foreignNumeric = **real**(foreignString)
destring foreignString, **gen**(foreignNumeric)
encode foreignString, **gen**(foreignNumeric) "foreign"

recast double mpg

generic way to convert between types

Summarize data

include missing values create binary variable for every rep78 value in a new variable, repairRecord

tabulate rep78, mi **gen**(repairRecord)

one-way table: number of rows with each value of rep78

tabulate rep78 foreign, mi

two-way table: cross-tabulate number of observations for each combination of rep78 and foreign

bysort rep78: **tabulate** foreign

for each value of rep78, apply the command **tabulate** foreign

table (foreign result) (), **stat**(mean price mpg) /*

/* **stat**(n price mpg) **nformat**(%6.1f mean)

create compact table of summary statistics

collect export table1.html

export table of summary statistics

dtbl price mpg i.rep78, **export**(table1.pdf)

create and export table of descriptive statistics

Create new variables

generate mpgSq = mpg^2 **gen** byte lowPr = price < 4000
create a new variable. Useful also for creating binary variables based on a condition (**generate** byte)

generate id = _n

bysort rep78: **gen** repairIdx = _n

_n creates a running index of observations in a group

generate totRows = _N **bysort** rep78: **gen** repairTot = _N

_N creates a running count of the total observations per group

pctile mpgQuartile = mpg, nq(4)

create quartiles of the mpg data

ege meanPrice = **mean**(price), **by**(foreign)

see **help egen** for more options

Data Transformation with Stata

Cheat Sheet

For more info, see Stata's reference manual (stata.com)

Select parts of data (subsetting)

SELECT SPECIFIC COLUMNS

drop make
remove the 'make' variable
keep make price
opposite of drop; keep only variables 'make' and 'price'

FILTER SPECIFIC ROWS

drop if mpg < 20 **drop in 1/4**
drop observations based on a condition (left)
or rows 1-4 (right)

keep in 1/30
opposite of drop; keep only rows 1-30

keep if inrange(price, 5000, 10000)
keep values of price between \$5,000–\$10,000 (inclusive)
keep if inlist(make, "Honda Accord", "Honda Civic", "Subaru")
keep the specified values of make

sample 25
sample 25% of the observations in the dataset
(use **set seed #** command for reproducible sampling)

Replace parts of data

CHANGE COLUMN NAMES

rename (rep78 foreign) (repairRecord carType)
rename one or multiple variables

CHANGE ROW VALUES

replace price = 5000 if price < 5000
replace all values of price that are less than \$5,000 with 5000

recode price (0 / 5000 = 5000)
change all prices less than 5000 to be \$5,000

recode foreign (0 = 2 "US") (1 = 1 "Not US"), gen(foreign2)
change the values and value labels then store in a new variable, foreign2

REPLACE MISSING VALUES

mvdecode _all, mv(9999) useful for cleaning survey datasets
replace the number 9,999 with missing value in all variables

mvencode _all, mv(9999) useful for exporting data
replace missing values with the number 9,999 for all variables

Label data

Value labels map string descriptions to numbers. They allow the underlying data to be numeric (making logical tests simpler) while also connecting the values to human-understandable text.

label define myLabel 0 "US" 1 "Not US"

label values foreign myLabel

define a label and apply it to the values in foreign

label list

list all labels within the dataset

note: data note here

place note in dataset


Reshape data

webuse set https://github.com/GeoCenter/StataTraining/raw/master/Day2/Data
webuse "coffeeMaize.dta" load demo dataset

MELT DATA (WIDE → LONG)

reshape variables starting with coffee and maize unique id variable (key) create new variable that captures the info in the column names

reshape long coffee@ maize@, i(country) j(year) — new variable
convert a wide dataset to long

WIDE **LONG (TIDY)**


CAST DATA (LONG → WIDE)

create new variables named coffee2011, maize2012... what will be unique id variable (key) create new variables with the year added to the column name

reshape wide coffee maize, i(country) j(year)
convert a long dataset to wide

xpose, clear varname
transpose rows and columns of data, clearing the data and saving old column names as a new variable called "_varname"

TIDY DATASETS have each observation in its own row and each variable in its own column.

When datasets are tidy, they have a consistent, standard format that is easier to manipulate and analyze.

Combine data

ADDING (APPENDING) NEW DATA
see help frames for using multiple datasets

webuse coffeeMaize2.dta, clear
save coffeeMaize2.dta, replace load demo data
webuse coffeeMaize.dta, clear

append using "coffeeMaize2.dta", gen(filenum)
add observations from "coffeeMaize2.dta" to current data and create variable "filenum" to track the origin of each observation

MERGING TWO DATASETS TOGETHER

must contain a common variable (id)

ONE-TO-ONE

webuse ind_age.dta, clear
save ind_age.dta, replace
webuse ind_ag.dta, clear

merge 1:1 id using "ind_age.dta"
one-to-one merge of "ind_age.dta" into the loaded dataset and create variable "_merge" to track the origin

MANY-TO-ONE

webuse hh2.dta, clear
save hh2.dta, replace
webuse ind2.dta, clear

merge m:1 hid using "hh2.dta"
many-to-one merge of "hh2.dta" into the loaded dataset and create variable "_merge" to track the origin

FUZZY MATCHING: COMBINING TWO DATASETS WITHOUT A COMMON ID

relink match records from different datasets using probabilistic matching **ssc install remlink**
jarowinkler create distance measure for similarity between two strings **ssc install jarowinkler**

Manipulate strings

GET STRING PROPERTIES

display length("This string has 29 characters")
return the length of the string

charlist make * user-defined package
display the set of unique characters within a string

display strpos("Stata", "a")
return the position in Stata where a is first found

FIND MATCHING STRINGS

display strmatch("123.89", "1???.??")
return true (1) or false (0) if string matches pattern

display substr("Stata", 3, 5)
return string of 5 characters starting with position 3

list make if regexm(make, "[0-9]")
list observations where make matches the regular expression (here records that contain a number)

list if regexm(make, "(Cad.|Chev.|Datsun)")
return all observations where make contains "Cad.", "Chev." or "Datsun"
compare the given list against the first word in make

list if inlist(word(make, 1), "Cad.", "Chev.", "Datsun")
return all observations where the first word of the make variable contains the listed words

TRANSFORM STRINGS

display regexpr("My string", "My", "Your")
replace string1 ("My") with string2 ("Your")

replace make = subinstr(make, "Cad.", "Cadillac", 1)
replace first occurrence of "Cad." with Cadillac in the make variable

display strtrim(" Too much Space")
replace consecutive spaces with a single space

display trim(" leading / trailing spaces ")
remove extra spaces before and after a string

display strlower("STATA should not be ALL-CAPS")
change string case; see also **strupper**, **strproper**

display strtoname("1Var name")
convert string to Stata-compatible variable name

display real("100")
convert string to a numeric or missing value

Save & export data

compress

compress data in memory

save "myData.dta", replace Stata 12-compatible file
saveold "myData.dta", replace version(12)
save data in Stata format, replacing the data if a file with same name exists

export excel "myData.xls", /*
*/ firstrow(variables) **replace**
export data as an Excel file (.xls) with the variable names as the first row


export delimited "myData.csv", delimiter(",") replace
export data as a comma-delimited file (.csv)

Data Visualization with Stata

Cheat Sheet

For more info, see Stata's reference manual (stata.com)

ONE VARIABLE



histogram mpg, width(5) freq kdensity kdenopts(bwidth(5))

kdensity mpg, bwidth(3)
smoothed histogram
bwidth • kernel(<options>) • normal • normopts(<line options>)

main plot-specific options;
see help for complete set


DISCRETE




graph bar (count), over(foreign, gap(*0.5)) intensity(*0.5)
bar plot
graph hbar draws horizontal bar charts
(asis) • (percent) • (count) • over(<variable>, <options: gap(*) • relabel • descending • reverse>) • cw • missing • nofill • allcategories • percentages • stack • bargap(#) • intensity(*) • yalternate • xlabelname

graph bar (percent), over(rep78) over(foreign)
grouped bar plot
(asis) • (percent) • (count) • over(<variable>, <options: gap(*) • relabel • descending • reverse>) • cw • missing • nofill • allcategories • percentages • stack • bargap(#) • intensity(*) • yalternate • xlabelname


DISCRETE X, CONTINUOUS Y



graph dot (mean) length headroom, over(foreign) m(1, ms(S))
dot plot
(asis) • (percent) • (count) • (stat: mean median sum min max ...) over(<variable>, <options: gap(*) • relabel • descending • reverse sort(<variable>)) • cw • missing • nofill • allcategories • percentages linegap(#) • marker#, <options> • linetype(dot | line | rectangle) dots(<options>) • lines(<options>) • rectangles(<options>) • rwidth




graph hbox mpg, over(rep78, descending) by(foreign)
missing box plot
graph box draws vertical boxplots
over(<variable>, <options: total • gap(*) • relabel • descending • reverse sort(<variable>)) • missing • allcategories • intensity(#) • boxgap(#)
medtype(line | line | marker) • medline(<options>) • medmarker(<options>)



vioplot price, over(foreign)
violin plot
over(<variable>, <options: total • missing>) • nofill • vertical • horizontal • obs • kernel(<options>) • bwidth(#) • barwidth(#) • dscale(#) • ygap(#) • ogap(#) • density(<options>) bar(<options>) • median(<options>) • obsopts(<options>)


Plot placement

JUXTAPOSE (FACET)



twoway scatter mpg price, by(foreign, norescale)
msymbol(<symbolstylelist>) • mcolor(<colorstylelist>)
msize(<markersizestylelist>) • mlabel(<varlist>) • title(<tinfo>)
connect(<connectstylelist>) • legend(<contents> [location]) • name(name!, replace!) • saving(filename [, suboptions])

SUPERIMPOSE



graph combine plot1.gph plot2.gph...
combine two or more saved graphs into one plot
scatter trunk headroom rep78 price, msymbol(D O T)
mlabel(truck headroom rep78)
plot several y values for one x value
graph twoway scatter mpg price || scatter mpg price /* if
mpg < 15, mlabel(make) m(l) legend(label(2 "mpg<15"))
combine two-way plots using ||

BASIC PLOT SYNTAX:
graph <plot type> variables: y first
y₁ y₂ ... y_n x [in] [if], <plot options>
titles plot-specific options
xtitle("x-axis title") ytitle("y axis title") xscale(range(low high)) log reverse off noline yscale(<options>)
by(var) facet axes
xline(xint) yline(yint) text(y x "annotation")
custom appearance
<marker, line, text, axis, legend, background options>
scheme(s1mono) play(customTheme) xsize(5) ysize(4) saving("myPlot.gph", replace)
plot size save

TWO+ CONTINUOUS VARIABLES



graph matrix mpg price weight, half
scatterplot of each combination of variables
half • jitter(#) • jitterseed(#) • diagonal • aweights(<variable>))



twoway scatter mpg weight, jitter(7)
scatterplot
jitter(#) • jitterseed(#) • sort • cmissing(yes | no)
connect(<options>) • aweight(<variable>))



twoway scatter mpg weight, mlabel(mpg)
scatterplot with labeled values
jitter(#) • jitterseed(#) • sort • cmissing(yes | no)
connect(<options>) • aweight(<variable>))



twoway connected mpg price, sort(price)
scatterplot with connected lines and symbols
jitter(#) • jitterseed(#) • sort • cmissing(yes | no)
connect(<options>) • aweight(<variable>))



twoway area mpg price, sort(price)
line plot with area shading
sort • cmissing(yes | no) • vertical, • horizontal
base(#)



twoway bar price rep78
bar plot
vertical, • horizontal • base(#), barwidth(#)



twoway dot mpg rep78
dot plot
vertical, • horizontal • base(#), ndots(#)
dcolor(<color>) • dfcolor(<color>) • dcolor(<color>)
dsizel(<marker size>) • dsymbol(<marker type>)
dlwidth(<stroke size>) • dotted(yes | no)



twoway dropline mpg price in 1/5
dropped line plot
vertical, • horizontal • base(#)



twoway rcpasym length headroom price
range plot (y₁ ÷ y₂) with capped lines
vertical, • horizontal

see also rcp



twoway rarea length headroom price, sort
range plot (y₁ ÷ y₂) with area shading
vertical, • horizontal • sort
cmissing(yes | no)



twoway rbar length headroom price
range plot (y₁ ÷ y₂) with bars
vertical, • horizontal • barwidth(#), mwidth
msize(<marker size>)



twoway pspike wage68 ttl_exp68 wage88 ttl_exp88
Parallel coordinates plot
vertical, • horizontal
(sysuse nlswide1)



twoway pccapsym wage68 ttl_exp68 wage88 ttl_exp88
Slope/bump plot
vertical, • horizontal • headlabel
(sysuse nlswide1)

THREE VARIABLES



twoway contour mpg price weight, level(20) crule(intensity)
3D contour plot
ccuts(#s) • levels(#), minmax • crule(hue | chue | intensity | linear)
scolor(<color>) • ecolor(<color>) • colors(<colorlist>) • heatmap
interp(thinplatespline | shepard | none)



regress price mpg weight length turn, nocons
matrix regmat = e(V)
plotmatrix, mat(regmat) color(green) aspect(1) legend(off)
heatmap
mat(<variable>) • split(<options>) • color(<color>) • freq

SUMMARY PLOTS



twoway mband mpg weight || scatter mpg weight
plot median of the y values
bands(#)



binscatter weight mpg, line(none)
plot one value (mean or median) for each x value
medians • nquantiles(#), discrete • controls(<variables>)
linetype(lfit | qfit | connect | none) • aweight(<variable>)

FITTING RESULTS



twoway lfitci mpg weight || scatter mpg weight
calculate and plot linear fit to data with confidence intervals
level(#), stdp • stdf • nofit • fitplot(<plottype>) • ciplot(<plottype>)
range(#), n(#), atobs • estopts(<options>), predopts(<options>)




twoway lowess mpg weight || scatter mpg weight
calculate and plot lowess smoothing
bwwidth(#), mean, noweight • logit, adjust



twoway qfici mpg weight, alwidth(none) || scatter mpg weight
calculate and plot quadratic fit to data with confidence intervals
level(#), stdp • stdf • nofit • fitplot(<plottype>) • ciplot(<plottype>)
range(#), n(#), atobs • estopts(<options>), predopts(<options>)

REGRESSION RESULTS



regress price mpg headroom trunk length turn
coefplot, drop(cons) xline(0)
Plot regression coefficients
baselevels • b(<options>), at(<options>), noci • levels(#), keep(<variables>), drop(<variables>), rename(<list>)




regress mpg weight length turn
margins, eyex(weight), at(weight = (1800(200)4800))
marginsplot, nocl
Plot marginal effects of regression
horizontal, • noci

Plotting in Stata

Customizing Appearance

For more info, see Stata's reference manual (stata.com)



`scatter price mpg, graphregion(fcolor("192 192 192")) ifcolor("208 208 208")`

specify the fill of the background in RGB or with a Stata color

`scatter price mpg, plotregion(fcolor("224 224 224")) ifcolor("240 240 240")`

specify the fill of the plot background in RGB or with a Stata color

SYNTAX

marker
<marker options>

arguments for the plot objects (in green) go in the options portion of these commands (in orange)
for example:
`scatter price mpg, xline(20, lwidth(vthick))`

COLOR

`mcolor("145 168 208") mcolor(None)`
specify the fill and stroke of the marker in RGB or with a Stata color

`mfcolor("145 168 208") mfcolor(None)`
specify the fill of the marker

SIZE / THICKNESS

<code>msize(medium)</code>	specify the marker size:
	<code>ehuge</code>
	<code>vhuge</code>
	<code>huge</code>
	<code>vlarge</code>
	<code>large</code>
	<code>medlarge</code>
	<code>medium</code>
	<code>medsmall</code>
	<code>small</code>
	<code>vsmall</code>
	<code>tiny</code>
	<code>vtiny</code>


APPEARANCE

<code>msymbol(Dh)</code>	specify the marker symbol:
	<code>O</code>
	<code>D</code>
	<code>T</code>
	<code>S</code>
	<code>o</code>
	<code>d</code>
	<code>t</code>
	<code>s</code>
	<code>Oh</code>
	<code>Dh</code>
	<code>Th</code>
	<code>Sh</code>
	<code>oh</code>
	<code>dh</code>
	<code>th</code>
	<code>sh</code>
<code>+</code>	<code>X</code>
<code>*</code>	<code>p</code>
<code>.</code>	<code>none</code>
<code>i</code>	

POSITION

<code>jitter(#)</code>	randomly displace the markers
	set seed

ANATOMY OF A PLOT



Apply themes

Schemes are sets of graphical parameters, so you don't have to specify the look of the graphs every time.

USING A SAVED THEME

`twoway scatter mpg price, scheme(customTheme)`

help scheme entries Create custom themes by saving options in a .scheme file

see all options for setting scheme properties

adopath ++ " ~/<location>/StataThemes" set path of the folder (StataThemes) where custom .scheme files are saved


set as default scheme

set scheme customTheme, permanently change the theme

net inst brewscheme, from("https://wbuchanan.github.io/brewscheme/") replace install William Buchanan's package to generate custom schemes and color palettes (including ColorBrewer)

USING THE GRAPH EDITOR

`twoway scatter mpg price, play(graphEditorTheme)`



Save theme as a .grec file

Save plots

`twoway scatter mpg price, saving("Plot.gph", replace)`

save the graph when drawing

`graph save "myPlot.gph", replace`

save current graph to disk

`graph combine plot1.gph plot2.gph...`

combine two or more saved graphs into one plot

`graph export "myPlot.png", as(png)`

see options to set size and resolution
export the current graph as an image file